

Compliance Document

No. D 102650 0017 Rev. 00

Holder of Certificate: **Shanghai Sermatec Energy Technology Co.,Ltd.**
Room 601-602, Block A, No.399, ZhongRen Road
JiaDing District
201802 Shanghai
PEOPLE'S REPUBLIC OF CHINA

Product: **Converter
(Hybrid inverter)**

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290203060601

Date, 2020-10-28



(Billy Qiu)

Compliance Document

No. D 102650 0017 Rev. 00

Model(s): SMT-5K-TL-LV

Parameters:

PV terminal	
Vmax. PV	580 Vd.c.
MPPT voltage range	125~550Vd.c.
Max. continuous PV input current	11/11 Ad.c.
Isc PV	14/14 Ad.c.
Max. continuous PV input power	6000W
Battery terminal parameter	
Battery type	Li-ion
Voltage range	40-58 Vd.c.
Rated voltage	48 Vd.c.
Maximum charge/discharge current	70/100 Ad.c.
Maximum charge/discharge power	4200/4600 W
Grid terminal parameter	
Rated voltage	230 Va.c.
Rated frequency	50 Hz
Rated input current	21.7 Aa.c.
Maximum continuous input current	22.7 Aa.c.
Maximum continuous input power	5000 W
Rated output current	21.7 Aa.c.
Maximum continuous output current	22.7 Aa.c.
Power factor (Cos phi), adjustable	0.8leading~0.8lagging
Maximum continuous output power	5000W
Backup load terminal parameter	
Rated voltage	230 Va.c.
Rated frequency	50 Hz
Rated output current	21.7 Aa.c.
Maximum continuous output current	22.8 Aa.c.
Maximum continuous output power	4600W

Tested according to:

EN 50549-1:2019/AC:2019
NTS V1.0:2019-07